



LOBADUR®

# 2K Supra

ADVANCED  
TECHNOLOGY

Ceramic-reinforced waterbased 2-component polyurethane finish for wooden floors

**Super durable, Supra scratch-resistant – ready for full use after 12 hours!**

The most scratch-resistant waterbased finish on the market – for long-lasting protection and a rich surface

Do you have high expectations? So do we! Choose 2K Supra A.T. with optimized formula and benefit from an extremely resistant and durable surface. Make use of the time advantage: the finished floor can be fully used after only 12 hours.

Optimized  
Formula



LOBA – Your partner for surface finishing and care

## Why end users are convinced of 2K Supra A.T.:

- Long-lasting flooring thanks to optimized protection against scratches and high resistance
- Can be fully used after only 12 hours
- Very low emissions
- Increased slip resistance

## Why contractors are enthusiastic about 2K Supra A.T.:

- Excellent flow and wetting properties due to an optimized formula
- Excellent scratch-resistance thanks to innovative ceramic reinforcement
- Excellent resistance against chemicals, friction and wear
- Can be fully used after 12 hours
- Very low emissions, EMICODE® EC1
- Coefficient of sliding friction > 0.5 according to DIN 18032 for sports flooring
- FIBA approved for basketball floors: variant satin

## Special feature

The ceramic-reinforced parquet finish provides an extremely scratch-resistant surface and offers long-lasting protection.

## Range of use

Perfect for demanding and high-traffic floors, such as in restaurants, shops and sports halls. Suitable for parquet, wooden floors as well as cork, linoleum and PVC coverings. Achieves the coefficient of sliding friction according to DIN 18032 for sports flooring. For extremely heavy use.

## Application


- Professionally sand and de-dust the substrate
- Apply primer as specified in TI
- First coat of 2K Supra A.T. with the LOBAT00L Deluxe 120 roller or Microfibre 100–120 roller
- Intermediate sanding after 4 hours with LOBASAND P180 perforated pad or finer for the semi-matte version, or the P120 perforated pad for the matte version
- Second coat of 2K Supra A.T. with the LOBAT00L Deluxe 120 roller or Microfibre 100–120 roller
- Consumption quantity per application: 100–120 g/m<sup>2</sup> with the LOBAT00L Deluxe 120 roller or 80–100 g/m<sup>2</sup> with the Microfibre 100–120 roller



**Article no. 11465**

**Available in satin and semi-gloss (5kg)**

**GISCODE W3/DD+**



LOBA is always at your side and ensures your success with both advice and action. Our experienced application specialists will advise you personally with your projects. Our competent service team is quickly on hand if you need practical support directly on site. So you can be on the safe side right from the start and know who you can rely on at all times.

**Please consider the detailed technical information, application advices and set-up recommendations.**

Technical information



**LOBA GmbH & Co. KG**

Leonberger Str. 56–62 | 71254 Ditzingen | Germany | Tel: +49 7156 357-0 | Fax: +49 7156 357-211 | E-Mail: [service@loba.de](mailto:service@loba.de) | [www.loba.de](http://www.loba.de)