

excellent
protection
for years
to come...

waterborne
finishing
systems

WS 2K Duo

two component waterborne
polyurethane timber finish

Loba 2K Duo is an extremely durable, low VOC, low odour, non yellowing and fast curing water-based system that provides excellent enhancement and protection for commercial or domestic timber flooring installations.



MADE IN GERMANY
SINCE 1922

ADVANCED
TECHNOLOGY

WS 2K Duo

two component waterborne polyurethane timber finish

Loba WS 2K is a two component water borne polyurethane timber finish that delivers excellent performance in both commercial or domestic timber flooring situations.

Loba WS 2K Duo is one of a new era of waterborne floor coatings combining extreme durability and wear resistance with a silky smooth attractive finish. Loba 2K Duo is also extremely low VOC so its easy on the nose and easy on the environment.

Loba WS 2K "Duo" comes in a specialised range of finishes with ultra modern "invisible protection" to traditional gloss finishes, and when used in conjunction with one of the Loba timber primers will enhance the colour, retain the natural appearance and beauty of your timber, reduces the risk of edge-bonding and provide a choice of stylish looks with the maximum protection expected of a Loba coating system.

Loba WS Duo is super easy to use, dries and hardens fast so the job is finished quick and with less airborne dust/matter to spoil the finish. Loba WS Duo is ideal for all application environments with no need to worry about exposure to harsh solvents and eliminates the need to vacate premises for extended periods.

Loba WS 2K DUO advantages at a glance:

- Non-yellowing
- 100% polyurethane
- Non-flammable
- Fast drying (1 hour dust free, 4 hour dry film) at 20°C
- Extremely wear resistance commercial grade finish
- Wide range of Natural looking finishes with "Invisible protection", satin-matt, semi-gloss, gloss and extra-matt sheen levels.
- Slip resistant to Australian Standard AS/NZS 4586:2013 – P3
*2K Duo Anti Slip R10 available for stairs meets AS P4 & German ramp standard R10 and is perfect for stairs and slippery areas.
- Extremely Low VOC with only 49/L grams per kg complies with the Green Building Council Australia requirement
- Superior adhesion properties makes the 2K Duo/2K contact system ideal for re-coating most solid and engineered timber surfaces

Why Loba WS 2K Duo ?

waterborne

extremely low VOC, 100% polyurethane with low odour.

strength:

extreme wear resistance, suits commercial / domestic application on solid and engineered timber floors, cork and parquetry

fast:

light foot traffic after just 12 hours
general foot traffic 24 hrs

colour:

various sheens and colour effects can be achieved when used in conjunction with one of the specialist Loba timber primers to enhance and control the colour of the timber

sheen levels:

Extra - Matt
Matt - Satin
Semi-gloss
Gloss
Anti-Slip R10/P4

connected:

System warranties when used in conjunction with Wakol flooring installation products.



Loba®
On Top!

Loba Australasia Pty Ltd

1300 PH LOBA

1 3 0 0 7 4 5 6 2 2

email: info@loba.com.au

6 Strong Ave,
Thomastown, Victoria
Australia 3074

web: www.loba.com.au

