

## LOBASOL<sup>®</sup> Deck & Teak Oil



### Product description

Special oil for outdoor use basing on vegetable oils. Due to its good penetration properties the wood will be preserved, but remains vapor-permeable. The woods natural texture and beauty will be accentuated. The friction values according to class R10 of BGR 181 and DIN 51130 will be achieved.

### Range of Use

To impregnate outdoor garden furniture, decks and other objects made of teak and other wood species.

### Features

- Good penetration behavior
- Basing on vegetable oils
- Increased UV-light resistance
- Excellent weather-resistance
- Easy to apply
- Also suitable for the impregnation of garden furniture

### Technical Data

<b>Article No.</b>	10615	<b>Application Rate</b>	Softwood: 200-250ml/m <sup>2</sup> Hardwood: 100-120ml/m <sup>2</sup>
<b>Package Size</b>	Transparent 10l, 2,5l, 0,75l Color 2,5l, 0,75l	<b>Application Tool</b>	Paintbrush, LOBATOOL Oil brush, non-fluffy cloth
<b>Packing</b>	Box: 1 x 12l Pallet: 42 x 12l Box: 4 x 2,5l Pallet: 120 x 2,5l Box: 6 x 0,75l Pallet: 432 x 0,75l	<b>Drying Time</b>	Walk on After 12 h
<b>Storage and Transportation</b>	Not sensitive to frost, storable for 36 months, no hazardous material according to ADR	<b>Thinner</b>	Do not dilute. Product is ready to use.
<b>Giscode</b>	Ö 60	<b>Full declaration</b>	Refined vegetable oils (sunflower oil, wood oil, linseed oil), silicic acid, drying agents (lead-free), antioxidant (free from phenol and oxime), white spirit (de-aromatized, purified)

Store soaked cloth, pads and other tools in closed containers. Sanding dust, cloths, etc. contaminated with oil / wax must be wetted with water, stored in a lockable container or disposed fire-proofely in another way.  
**Otherwise danger of self-ignition.**

### Color (without color guarantee)



Light Bangkirai    Dark Bankirai    Douglas fir    Garapa

# LOBASOL<sup>®</sup> Deck & Teak Oil

### Information on Use:

- Shake material well
- Regard safety regulations
- \*) Regard General Information on the use LOBASOL<sup>®</sup> products

### Preparation:

For the application an outdoor-temperature at least 10°C is required. Wood that should be impregnated has to be clean and dry. If required remove soilings, moss and old coatings.

### Newly installed, widely dense porous woods

are often not capable to absorb sufficient amounts of oil, therefore first of all the pores of the wood have to be opened. This can be caused by outdoor weathering or alternatively by repeated watering (let the wood dry completely after each watering process).

### Old heavily soiled and weathered wooden terraces and decks

can be brushed automatically, for example with the machine **FG Terrassen-Blitz** and **FG Terrassen-Randy** for edges and small areas.

**Alternatively** perform an **intensive cleaning** with LOBA ParkettSoap,

- mix ParkettSoap in a ratio of 1 : 2 with water
- damp surface and work surface with brush or scrubber
- rinse dissolved dirt with water
- apply Deck & Teak Oil after complete drying

When using a high-pressure cleaner regulate the pressure to ensure the wood surface won't be damaged.

### Application:

1. Apply Deck & Teak Oil in the direction of the woods graining with a non-fluffy cloth.
2. Remove excessive material completely after about 30 minutes penetration time by spreading with a brush or with a non-fluffy cloth.
3. On garden furniture especially on chairs, use absorbent cloths to remove any excessive oil until the surface is almost completely dry.
4. Use LOBATool oil brush on larger areas.
5. If necessary repeat procedure after drying overnight.

### Notice:

Before using Deck & Teak Oil Color we recommend to establish a sample area to test the desired color result and appearance of the surface. The different colors can be mixed among each other. In order to achieve a more transparent color Deck & Teak Oil transparent can be added.

**The general information on the use of LOBASOL<sup>®</sup> products are part of this information and must be noticed.**