



WOCA WOODCARE

📞 877-962-2645 ✉ info@wocawoodcare.com

WOCA MAINTENANCE GEL - APPLICATION INSTRUCTIONS

WOCA Maintenance Gel is for "re-oiling" oiled wood surfaces which restores and refinishes oiled wood floors. WOCA Maintenance Gel may also be used as a topcoat on an oiled floor to achieve a satin sheen.

Maintenance Gel is available in Natural and White.

Product, room and floor temperature should be at least 59 degrees. Ensure good ventilation during application and drying time.

Work Instructions:

When using as a Maintenance Coat

Damp mop the floor with WOCA Intensive Wood Cleaner (dilute 3 ounces of WOCA Intensive Wood Cleaner to 1 gallon of lukewarm water). Let the floor dry completely. *This is a mandatory step that deep cleans the oiled wood surface and preps it for the gel application.*

When using to raise the sheen on a new floor

WOCA Intensive Wood Cleaner is not necessary *unless* the floor has been exposed to traffic.

1. Apply WOCA Maintenance Gel onto a white polishing pad in a circular motion, using approx. a quarter of the tube.
2. Polish Maintenance Gel uniformly into the floor using a standard buffer. Continue buffing until the wood appears saturated and silky matte. Apply more gel as necessary.
3. After gel has been applied, polish the entire floor well with polishing cloths or terry cloth towels to remove excess Gel. There should be no excess Gel on the surface.
4. The Maintenance Gel will normally dry in 4-6 hours.
5. Do not expose floor to water for 2-3 days after finishing.
6. After 3 days the floor may be treated with WOCA Natural Soap to provide additional protection against wear and tear.

Tip: For fastest drying time, leave windows slightly open to ensure a steady flow of fresh oxygen.

Spread Rate: 215-320 s.f./tube

Warning! Rags, pads or waste soaked with WOCA oil may self-ignite if improperly discarded. Immediately after use, place all rags and waste in a sealed, water filled bucket for proper disposal.