

Technical data sheet

1815 siatop



Status:	Ok
Approval:	24.01.2022

Classification	
	Public series
Product type:	Coated abrasives
Main industries:	General Fabrication Aerospace
Further industries:	Trucks Rail Marine Bus Wind Power Machinery, equipment Coils and Sheet Metal Machinery, equipment Tubes and Profiles






Product profile	
Grit type:	Zirconia alumina
Grit range (total):	24; 36-320; 400 P100 – P400 FEPA P / ISO 6344 24 – 80 ANSI
Backing:	Fibre, f-wt paper (FSC-certified)
Coating:	Closed
bonding:	Resin over resin
Special coating:	Cooling top coat
Equipment:	





Properties		Technology
Removal rate:	8 - high	- Plain - siafast
Lifetime:	8 - long	
Finishing:	9 - very good	
Flexibility:	3 - rigid	
Contact pressure:	7 - strong	

Advantages	
General Fabrication:	<ul style="list-style-type: none"> - Versatile all-round product with an attractive range of options - Outstanding performance in dry sanding applications - Fast and rugged stock removal with regular surface quality - Cost reduction thanks to long lifetime - Minimal effort required for high stock removal - Excellent surface quality
Aerospace:	<ul style="list-style-type: none"> - Outstanding performance in dry sanding applications - Fast and safe change of abrasive with siafast hook and loop fastening system - The low-cost alternative to fibre discs - Minimal effort required for high stock removal

Applications	
General Fabrication:	<ul style="list-style-type: none"> - Removal of paint - Removal of rust - Weld preparation - Removing discolouration - Sanding down - Deburring - Surface finishing - Smoothing and blending of flaws - Structuring and final sanding
Aerospace:	<ul style="list-style-type: none"> - Removal of paint - Removal of rust - Weld preparation - Removing discolouration - Sanding down - Surface finishing - Deburring

Material		
General Fabrication:	Non-ferrous metals Stainless steel Steel	<input type="radio"/> Non-ferrous metal <input type="radio"/> High alloyed steel <input checked="" type="radio"/> Unalloyed / low-alloy steel
Aerospace:	Composites	<input checked="" type="radio"/> Composite

Conversion forms	Upper conversion	Lower conversion
	Rolls	- Jumbo rolls
	Strips	- siafast strips
	Delta and polygons	- Delta and polygons
	Discs	- siafast discs - Various discs
	Belts	- Narrow, edge and long belts (width: 25-399 mm/length: up to 8500 mm)

Application	Superordinate group	Subgroup
	Portable machine sanding	Angle grinders
	Portable machine sanding	random orbital sander
	Stationary belt sanding	Contact wide belt sanding
	Stationary belt sanding	Long belt sanding

Technical data sheet

1815 siatop



Application	Superordinate group	Subgroup
	Stationary machine sanding	Stationary disc sanding
cut:	Dry applications	

Details	
No suitability for:	<ul style="list-style-type: none"> - In heavy duty use - glass sanding - Wet sanding - stone grinding
Sanding recommendation:	<ul style="list-style-type: none"> - Designed for universal use thanks to co-ordinated product parameters - Good adhesion of velcro backing to the new siatop siafast sanding pad
Safety recommendation:	<ul style="list-style-type: none"> - Pay attention to the abrasives safety data sheet (available from sia Abrasives) - Follow the general FEPA safety recommendations - Use eye and face protection - Use an effective dust extraction unit or wear a fine dust mask

Communication			
Claim:	For fast and cost-effective surface treatment of steel and non-ferrous metals		
Copy:	1815 siatop impresses with its high removal rate, long lifetime and very good finish.		
Image material:	Product Top View (PTV)	Front side: ID	Rear side: ID
	Application image	General Fabrication: ID 5617	Aerospace: ID 6385
	Product show:		
	Macro shot:		
	Packaging image:		
	Product group image:		ID 12285

- Main application
- Secondary application