

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 3 (replaces version 2)

Revision: 22.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Product name** SlipResist
- **Article number:** 11018-000
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Additional component
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
LOBA GmbH & Co. KG
Leonberger Straße 56 - 62
D-71254 Ditzingen
- Tel.: +49 (0)7156/357-0
- **1.4 Emergency telephone number:**
Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The product is not classified, according to the GB CLP regulation.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Additional information:**
EUH208 Contains methyl methacrylate, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.
EUH210 Safety data sheet available on request.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture of the substances listed below with harmless additions.

· **Dangerous components:**

CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28	methyl methacrylate ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<1%
CAS: 55965-84-9 EC number: 911-418-6 Index number: 613-167-00-5 Reg.nr.: 01-2120764691-48	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) ⚠ Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; ⚠ Skin Corr. 1C, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Skin Sens. 1A, H317 Specific concentration limits: Skin Corr. 1C; H314: C ≥0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.00025-<0.0015%

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 3 (replaces version 2)

Revision: 22.11.2022

Product name SlipResist

(Contd. of page 1)

· **Additional information** For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** The product is not skin irritating.
- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing** In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or water bodies.
Inform respective authorities in case product reaches water or sewage system.
Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special precautions necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Storage class** 12
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 3 (replaces version 2)

Revision: 22.11.2022

Product name SlipResist

(Contd. of page 2)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Components with critical values that require monitoring at the workplace:**

80-62-6 methyl methacrylate

WEL Short-term value: 416 mg/m³, 100 ppm

Long-term value: 208 mg/m³, 50 ppm

· **Additional information:** The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures** Wash hands during breaks and at the end of the work.

· **Breathing equipment:** Not required.

· **Hand protection**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.4 mm

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

Value for the permeation: Level ≤ 6

· **Eye/face protection** Safety glasses recommended during refilling.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· **General Information**

· **Physical state**

Fluid

· **Colour:**

White

· **Smell:**

Recognisable

· **Odour threshold:**

Not determined.

· **Melting point/freezing point:**

Not determined

· **Boiling point or initial boiling point and boiling range**

100 °C (7732-18-5 water, distilled, conductivity or of similar purity)

· **Flammability**

Not applicable.

· **Lower:**

Not determined.

· **Upper:**

Not determined.

· **Flash point:**

Not applicable

· **Decomposition temperature:**

Not determined.

· **pH at 20 °C**

8.5

· **Viscosity:**

· **Kinematic viscosity**

Not determined.

· **dynamic at 20 °C:**

6,000 mPas

· **Solubility**

· **Water:**

Fully miscible

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 3 (replaces version 2)

Revision: 22.11.2022

Product name SlipResist

(Contd. of page 3)

· Partition coefficient n-octanol/water (log value)	Not determined.
· Steam pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C	1.111 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Self-inflammability:	Product is not selfigniting.
· Explosive properties:	Product is not explosive.
· Solids content:	60.0 %
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity

· LD/LC50 values that are relevant for classification:

55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

Oral	LD50	457 mg/kg (rat)
------	------	-----------------

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 3 (replaces version 2)

Revision: 22.11.2022

Product name SlipResist

(Contd. of page 4)

Dermal	LD50	660 mg/kg (rat)
Inhalative	LC50/4 h	0.33 mg/l (rat)
	LC50/96 h	0.188 mg/L (fish)

· **11.2 Information on other hazards**· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information· **12.1 Toxicity**· **Aquatic toxicity:**

55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

EC50/48 h	0.1 mg/L (daphnia)
EC50/72 h	0.027 mg/L (Algae)
NOEC	0.0012 mg/L (Algae)
	0.004 mg/L (daphnia)
	0.098 mg/L (fish)

· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**· **Additional ecological information:**· **General notes:** Generally not hazardous for water.**SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

· **Uncleaned packagings:**· **Recommendation:** Disposal must be made according to official regulations.· **Recommended cleaning agent:** Water, if necessary with cleaning agent.**SECTION 14: Transport information**· **14.1 UN number or ID number**· **ADR, IMDG, IATA**

Void

· **14.2 UN proper shipping name**· **ADR, IMDG, IATA**

Void

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 3 (replaces version 2)

Revision: 22.11.2022

Product name SlipResist

(Contd. of page 5)

· 14.3 Transport hazard class(es)	
· ADR, ADN, IMDG, IATA	
· Class	Void
· 14.4 Packing group	
· ADR, IMDG, IATA	Void
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations**
- **Water hazard class:** Generally not hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (*).

- **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H301 Toxic if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

- **Department issuing data specification sheet:** Productmanagement.

- **Abbreviations and acronyms:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids – Category 2

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 22.11.2022

Version number 3 (replaces version 2)

Revision: 22.11.2022

Product name SlipResist

(Contd. of page 6)

*Acute Tox. 3: Acute toxicity – Category 3**Acute Tox. 2: Acute toxicity – Category 2**Skin Corr. 1C: Skin corrosion/irritation – Category 1C**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Skin Sens. 1: Skin sensitisation – Category 1**Skin Sens. 1A: Skin sensitisation – Category 1A**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*** Data compared to the previous version altered.*

GB