



# Wood Lye

## Minimizes yellowing of the wood

Wood Lye is used for priming of untreated or newly sanded interior woodwork like floors, stairs, furnitures and panels. The priming minimizes yellowing of the wood and highlights the wood structure creating a coloured wash effect, depending on the chosen colour. Wood Lye is suitable for all types of wood.

- Minimizes the yellowing process of the wood
- For a lighter finish
- Combination with oil, lacquer or soap as finish
- Suitable for any type of wood

### Application area

Used for priming of unfinished and newly sanded interior wood. Ideal for all types of wood. Requires subsequent treatment with oil, lacquer or soap.

### Work description

#### Preparation

The unfinished woodwork must be clean, dry and finely sanded (grit 100-120) before applying the lye.

#### Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

#### Treatment

Shake the container well and pour the lye into a plastic bucket. It is important that no pigments are left in the container. Stir regularly during the application to prevent the pigments from settling to the bottom. Apply an even coat of the lye with the WOCA Applicator, a nylon brush or roller lengthwise along the grain. Apply at least 1 L of lye per 10 m<sup>2</sup> of wood. Leave wood to dry for approx. 8-12 hours at 20°C. De-nib standing fibres and remove excess pigments with a medium e.g. green or bordeaux, sanding polishing pad. Remove the sanding dust with a vacuum cleaner. Finish the wood surface with a WOCA oil, lacquer or soap.

### Drying time

**Drying time:** 8-10 hours at 20°C

### Technical data

**Declaration:** 1,2-benzisothiazol-3(2H)-one

**VOC:** 10 g/l, maximum VOC content (A/g (WB)): 30 g/l.

**Density:** 1.00-1.10 g/ml.

**pH-value:** pH 8-9

**Shelf life:** 3 years

**Application Temperature:** +15-30°C and approx. 50% air humidity.

**Coverage:** 8-10 m<sup>2</sup>/L

**Colours:** White, Grey

**Cleaning of tools:** Use water

**Storage:** +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

**Packaging:** 2.5 L

**Dilution:** Undiluted

## Maintenance and related products

WOCA Denmark A/S  
Tværvej 6  
DK - 6640 Lunderskov  
+45 9958 5600  
info@wocadenmark.com  
wocadenmark.com

*This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.*