

Invisible Oil Care



Top coat and care for Invisible Oil

Invisible Oil Care is a water-based care product for the maintenance of surfaces that have been treated with WOCA Invisible Oil. This care product refreshes the oiled surface and increases the oil's ability to resist stains and wear. Invisible Oil Care is part of a high quality water-based oiling system and should therefore be used together with WOCA Invisible Oil Primer and Invisible Oil. The Invisible system has been developed for use with light wood varieties, where a high oiling quality and newly-sanded, untreated appearance are required. The range gives the floor a surface that is both comfortable to walk on and soft to the touch. The floor is also left with a soft, water-resistant surface that is easy to clean and maintain.

- Cares for and maintains floors that have been treated with Invisible Oil Primer and Invisible Oil
- Resistant to liquids such as water, coffee, tea and red wine
- Gives the wood a beautiful, breathable soft feel surface

Application area

For care and maintenance of wooden surfaces that have been treated with Invisible Oil Primer and Invisible Oil. The Invisible system has been developed for use with light wood varieties, where a high oiling quality and newly-sanded, untreated appearance are required. The range gives the floor a surface that is both comfortable to walk on and soft to the touch. The floor is also left with a soft, water-resistant surface that is easy to clean and maintain.

Work description

Preparation

It is important that the product, the room and the floor are at a temperature between 15 °C and 30 °C and that air humidity is approx. 50 %. Wood humidity must not exceed 12%. Make sure that the room is well-ventilated for optimal evaporation and drying time. Clean the surface using WOCA Intensive Wood Cleaner and leave until completely dry.

Always Remember

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Thoroughly shake the container, both before and during use. Apply Invisible Oil Care in a thin and even coat, using the WOCA Oil applicator or a wool pad and pad holder. Work in small areas of no more than 20 m² at a time. Carefully polish the area with a white pad. Use a buffing machine for larger surfaces. Continue polishing until the wood is completely saturated and the surface has a uniform appearance. Remove excess oil care with dry, lint-free

cotton cloths or pads attached to the buffing machine until the surface no longer appears wet. The surface can be used with caution after 6-12 hours and is fully hardened after 5 days at room temperature.

Please note

Do not expose the floor to water or other liquids for the first 5 days, while Invisible Oil Care is hardening. For optimal cleaning, we recommend WOCA Natural Soap Extra White, which cares for and maintains the surface.

Drying time

Drying time: 6-12 hours at 20°C

Fully hard: 5 days at 20°C

Technical data

VOC: 5 g/l, maximum VOC content (A/i (WB)): 140 g/l.

Density: 1.00-1.10 g/ml.

pH-value: pH 7-8

Shelf life: 3 years

Application Temperature: +15-25°C and approx. 50% air humidity.

Coverage: 30-40 m²/L

Colours: Natural

Cleaning of tools: Use warm water

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer.

Packaging: 1 L

Viscosity: 25-30 Sec. DIN Cup 4

Dilution: Undiluted

Odour: Faint

Solid content: 10-20%

Maintenance and related products

Maintaining and cleaning

For daily cleaning, WOCA Natural Soap is recommended, which effectively washes and cares for the wood. Supplement occasionally with WOCA Oil Refreshing Soap, which also adds a little oil to the wood with each wash.

Maintenance and related products

Invisible Oil Care, #525510

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.