

DeckDegrayer



REMOVER



Back to Start: Undo the weathering of your wood!

Special cleaner for wooden surfaces in outdoor areas. Renovation without sanding! LOBA DeckDegrayer brings back the natural color of wood. Use the biodegradable special cleaner for your terrace deck, garden furniture and wooden objects. The ideal pre-treatment before the application of LOBA DeckPrepare as well as LOBA DeckOil or LOBA DeckFinish Color.

- Ideal degreasing preparation for follow-up treatment
- Easy and safe application
- Can be used on horizontal and vertical surfaces and garden furniture, does not drip
- No sanding necessary
- Applicable to all wood species

Range of use:

Suitable for use on exterior wooden surfaces. Degray old oiled terrace decks. Clean and prepare old finished terrace deck for re-finishing. Newly laid deck, open pores, wash out wood ingredients from surface.

Technical Data

ART.-NO.			
10741	2.5l	6	144

pH	2.7
Contents	< 5% non-ionic surfactants, METHYLCHLOROISOTHIAZOLINONE AND METHYLISOTHIAZOLINONE (3:1)
Storage and transportation	36 months of storage stability. No hazardous material according to ADR. Store and transport between +5 to +25°C. Protect from frost.
GISCODE	GG10

Application

THREE AREAS OF APPLICATION, ONE PROCEDURE.

Degrayer old oiled terrace decks

- The special formulation allows to remove wood graying.

Clean and prepare old finished terrace deck for re-finishing

- Optimal preparation for secure adhesion of the subsequent finish layer.

Newly laid deck, open pores, wash out wood ingredients from surface

- Woods with a high content of wood ingredients, especially coniferous and exotic woods, tend to accumulate on the surface of the wood, e.g. teak that has not been freshly sanded even feels oily.
- In order to achieve an optimal bond between our products and the wood, these wood ingredients, resins and oils, must be washed off the surface. This opens the pores of the wood surface as well and the products can be better absorbed.
- Shake the contents well.
- Do not work under direct Sun influence. Moisten the surface with water in advance to ensure that the product does not dry too quickly.
- Observe general and, if necessary, product-specific occupational health and safety regulations. Further information can be found in the GISCODE-related operating instructions which are available under www.wingis-online.de.

THINNER / MIXING

The product is ready for use and must not be reduced!

APPLICATION TOOL / APPLICATION RATE

Brush or LOBA oilbrush / approx. 150-200 ml/m² (5-6 m²/l). Determine the exact consumption with a test application.

APPLICATION

- Remove loose dirt with broom in advance.
- Moisten the surface with water first to prevent LOBA Degrayer from drying too quickly.
- Apply LOBA DeckDegrayer undiluted with a brush or LOBA oil brush to the wood to be cleaned.
- Allow material to react for approx. 10 minutes.
- For process the surface, we recommend a cleaning machine suitable for wooden decks (automatic suction and scrubbing machine, high-pressure cleaner with corresponding attachment, etc.). Alternatively, use a scrubber or brush to work the surface along the wood grain.
- Then rinse the entire surface with clear water or spray it with a garden hose. In case of very stubborn soiling, repeat the treatment or allow LOBA DeckDegrayer to work for a longer time.
- After drying, optionally break up wood fibers with a steel broom or disc machine and LOBASAND SuperPad green to achieve a smoother surface. Re-oil with LOBA DeckOil or coat with LOBA DeckPrepare and LOBA DeckFinish, according to Technical Information on the product.

General guidelines

Cleaning of tools: Clean tools and equipment immediately with water.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

Drying time: The indicated drying times are valid for +20°C and 50% relative humidity, and assume careful, draught-free ventilation of the working area. Lower temperatures, higher relative humidity or poorer ventilation lead to longer drying times. Do not apply any protective coverings or wet clean the surface until full curing is achieved. Product-specific data can be found in the relevant technical information.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.