

Article Print d Versio	ate: 0	P389R80CK10 5.04.2023 .0001	AquaSeal NordicW Revision date: 17.03.2	03.2023	EN Page 1 / 8	
					e company/undertaking	
			Substance/mixte		ie company/undertaking	
1.1.	Product iden Article No. (ma Trade name/d	anufacturer/suppl	ier)	XP389R800 AquaSeal N		
1.2.		-	e substance or mi	-	s advised against	
		<b>ntified uses</b> aint related mater ndustrial and pro				
	Uses advised Do not use for	l <b>against</b> injecting or sprag	/ing.			
1.3.	Details of the	supplier of the	safety data sheet			
	Berger-Seidle Parkettlacke - Maybachstraß 67269 Grünsta Germany	GmbH Klebstoffe - Bauc e 2		Telephone:	r <b>)</b> +49 6359 / 8005-0 9 6359 / 8005-170	
	Laboratory		normation.			
	E-mail			Sicherheitso	laten@berger-seidle.de	
1.4.	24-hour emerg (BLG)	elephone numbe gency number: +4 gency number in s	9 700 24112112	388271 or +11	49 700 24112112 (BLG)	
SEC	FION 2: Haza	rds identificati	on			
2.1.	Classification	of the substan	ce or mixture			
	Classification	n according to R	egulation (EC) No	1272/2008 [CI	_P]	
	The mixture is	classified as not	hazardous accordir	ng to regulatior	n (EC) No 1272/2008 [CLP].	
2.2.	Label elemen	ts				
	Labelling acc	ording to Regul	ation (EC) No. 1272	2/2008 [CLP]		
	Hazard picto					
	Hazard state	<b>nents</b> not appli	cable			
	Precautionar		oublo			
	i roodutional	not appli	cable			
	Hazard comp	onents for label not appli	•			
	Supplementa EUH208		1,2-benzisothiazol-		action mass of 5-chloro-2- methyl-2H-isothiazo roduce an allergic reaction.	I-3-one and
	EUH210	Safety da	ata sheet available o	on request.		
2.3.	Other hazard	-				
	No information					
	Other informa Read label be children.		ical advice is need	led, have proc	duct container or label at hand. Keep out of	reach of
SEC	FION 3: Com	position/inforn	nation on ingredi	ents		
3.2.	Mixtures					
÷	Description	Water b	acad curfaca finicha	e colvent con	tent up to 15% N-methylpyrrolidope-free	

Description

Water-based surface finishes, solvent content up to 15%, N-methylpyrrolidone-free



1 - 2,5

Article No.: Print date: Version:	XP389R80CK10 05.04.2023 5.0001	AquaSeal NordicWhite Revision date: 17.03.2023 Issue date: 17.03.2023	EN Page 2 / 8	
Classific	ation according to F	Regulation (EC) No 1272/2008 [CLP]		
EC No.	REACH	No.		
CAS No.	Designa	ation		weight-%
Index No	. classifi	cation // Remark		
252-104-2	2 01-2119	9450011-60-XXXX		

Substance with a common (EC) occupational exposure limit value.

#### Additional information

Full text of classification: see section 16

#### **SECTION 4: First aid measures**

252-104-2 34590-94-8

#### 4.1. Description of first aid measures

#### **General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### **Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

- 4.2. **Most important symptoms and effects, both acute and delayed** In all cases of doubt, or when symptoms persist, seek medical advice.
- 4.3. Indication of any immediate medical attention and special treatment needed

(2-methoxymethylethoxy)propanol

First Aid, decontamination, treatment of symptoms.

#### **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Unsuitable extinguishing media

strong water jet

#### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

#### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

#### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

#### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.



Article No.:	XP389R80CK10	AquaSeal NordicWhite
Print date:	05.04.2023	Revision date: 17.03.2023
Version:	5.0001	Issue date: 17.03.2023

EN Page 3 / 8

#### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

#### **Further information**

Vapours are heavier than air. Vapours form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### Occupational exposure limit values:

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

WEL, TWA: 308 mg/m3; 50 ppm Remark: (may be absorbed through the skin)

#### Additional information

TWA : Long-term occupational exposure limit value STEL : short-term occupational exposure limit value Ceiling : peak limitation

#### DNEL:

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

DNEL long-term dermal (systemic), Workers: 283 mg/kg

DNEL long-term inhalative (systemic), Workers: 308 mg/m<sup>3</sup>

DNEL long-term dermal (systemic), Consumer: 121 mg/kg

DNEL long-term inhalative (systemic), Consumer: 37,2 mg/m<sup>3</sup>

DNEL long-term exposure oral (systemic effects), Consumer: 36 mg/kg

#### PNEC:

(2-methoxymethylethoxy)propanol

EC No. 252-104-2 / CAS No. 34590-94-8

PNEC aquatic, freshwater: 19 mg/L



Article No.:	XP389R80CK10	AquaSeal NordicWhite
Print date:	05.04.2023	Revision date: 17.03.2023
Version:	5.0001	lssue date: 17.03.2023

EN Page 4 / 8

PNEC aquatic, marine water: 1,9 mg/L PNEC aquatic, intermittent release: 190 mg/L PNEC sediment, freshwater: 70,2 mg/kg PNEC sediment, marine water: 7,02 mg/kg PNEC, soil: 2,74 mg/kg PNEC sewage treatment plant (STP): 4168 mg/L

#### 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

#### Personal protection equipment

#### **Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

#### Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber) Thickness of the glove material > 0.4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye/face protection

Wear closely fitting protective glasses in case of splashes.

#### Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state: Colour:	Liquid white
Odour:	characteristic
Odour threshold:	not applicable
Melting point/freezing point:	not applicable
Initial boiling point and boiling range:	<b>100 °C</b> Source: Water
Flammability:	not applicable
Lower and upper explosion limit: Lower explosion limit: Upper explosion limit:	<b>1,19 Vol-%</b> <b>14 Vol-%</b> Source: (2-methoxymethylethoxy)propanol
Flash point:	not applicable
Auto-ignition temperature:	<b>204 °C</b> Source: 2-(2-ethoxyethoxy)ethanol
Decomposition temperature:	not applicable
pH at 20 °C:	8 - 8,2 / 100,0 weight-%
Cinematic viscosity (40°C):	< 135 mm²/s
Viscosity at 20 °C:	25 s 4 mm



							Parkett Win blass
Article Print da Versior	ate:	XP389R80CK10 05.04.2023 5.0001	AquaSeal Nordi Revision date: 1 Issue date: 17.0	7.03.2023		EN Page 5 / 8	
				Method: D	DIN 53211		
	Solubility						
		lubility at 20 °C:	••	miscible			
	Partition coefficient: n-octanol/water: Vapour pressure at 20 °C:		ol/water:	see sectio	on 12		
	vapour pr	essure at 20 °C:		23 mbar Method: c Source: W			
	Density a Density a	nd/or relative densit t 20 °C:	ty:	<b>1,03 g/cm</b> <sup>3</sup> Method: 18	3 SO 2811, part 3		
	Relative v	apour density:		not applic	able		
	particle cl	haracteristics:		not applic	able		
	Other info						*
	Solvent so	eparation test:		< 3 weight	t-% (ADR/RID)		
SECT	FION 10: \$	Stability and react	tivity				
	Reactivity No informa	, ation available.					
	Chemical Stable who section 7.	•	mmended regulati	ons for stor	age and handling	g. Further informat	ion on correct storage: refer
		<b>y of hazardous reac</b> y from strong acids, s		strong oxidi	zing agents to av	oid exothermic rea	actions.
	Stable whe	<b>s to avoid</b> en applying the reco Hazardous decompo					ion on correct storage: refer
	Incompation not application	i <b>ble materials</b> able					
	Hazardous	s decomposition pr s decomposition byp rogen oxides.		with expos	ure to high temp	eratures, e.g.: cart	bon dioxide, carbon monoxic
SECT	<b>FION 11:</b> 1	Foxicological info	rmation				
11.1.	Informatio	on on hazard classe	es as defined in F	Regulation	(EC) No 1272/20	08	
	Acute tox			J			
	oral, LD5	ymethylethoxy)propa 0, Rat: > 5000 mg/kg .D50, Rabbit: > 5000	g				
	Skin corrosion/irritation; Serious eye damage/eye irritation						
	(2-methox Skin no irritati eyes	ymethylethoxy)propa on	nol				
	Respiratory or skin sensitisation						
	(2-methoxymethylethoxy)propanol						
				nd toxicity f	for reproduction	1)	
	CMR effects (carcinogenicity, mutagenicity and to Based on available data, the classification criteria are				-	,	
	STOT-single exposure; STOT-repeated exposure						
		ymethylethoxy)propa tion No data availabl					
	Asniration	hazard					

#### Aspiration hazard

(2-methoxymethylethoxy)propanol



Article No.:	XP389R80CK10	AquaSeal NordicWhite		
Print date:	05.04.2023	Revision date: 17.03.2023	EN	
Version:	5.0001	Issue date: 17.03.2023	Page 6 / 8	

Aspiration hazard; Evaluation Represents no obvious danger of aspiration due to its physical properties

#### Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

#### **Overall assessment on CMR properties**

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

#### 11.2. Information on other hazards

**Endocrine disrupting properties** No information available.

#### **SECTION 12: Ecological information**

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

(2-methoxymethylethoxy)propanol Fish toxicity, LC50, Pimephales promelas (fathead minnow): 10000 mg/L (96 h) Daphnia toxicity, EC50, Daphnia magna (Big water flea): 1919 mg/L (48 h)

#### Long-term Ecotoxicity

Toxicological data are not available.

#### 12.2. Persistence and degradability

(2-methoxymethylethoxy)propanol

: 75 % (28 D); Evaluation Readily biodegradable (according to OECD criteria).

Method: OECD F

: 93 % (13 D) Method: OECD 302B/ ISO 9888/ EEC 92/69/V, C.9

#### 12.3. Bioaccumulative potential

(2-methoxymethylethoxy)propanol Partition coefficient: n-octanol/water: 1,01

#### **Bioconcentration factor (BCF)**

Toxicological data are not available.

#### 12.4. Mobility in soil

(2-methoxymethylethoxy)propanol

: Evaluation No data available

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Endocrine disrupting properties

No information available. 12.7. **Other adverse effects** 

No information available.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

#### List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

# Safety Data Sheet

accoi	rding to Re	gulation (EU) 20	20/878	Berger	Scielle Parkett will das Beste!
Article Print c Versic	late:	XP389R80CK10 05.04.2023 5.0001	AquaSeal NordicWhite Revision date: 17.03.2023 Issue date: 17.03.2023	EN Page 7 / 8	
	Recommen		<b>ge</b> nay be recycled. Vessels not properly e	mptied are special waste.	
SEC.	TION 14: TI	ansport informa	tion	· ·	
		•	of this transport regulation.		
14.1.	UN number	or ID number			
			not applicable		
14.2.	UN proper	shipping name			
14.3.	Transport I	nazard class(es)			
	•	( )	not applicable		
14.4.	Packing gr	oup			
			not applicable		
14.5.		ntal hazards			
	•	ort (ADR/RID)	not applicable		
	Marine pollu		not applicable		
14.6.		cautions for user			
	case of an a	lways in closed, up accident or leakage safe handling: see		at persons transporting the product ki	now what to do ir
	Further info	ormation			
	I and trans	port (ADR/RID)			
	Tunnel restr		<u>-</u>		
	Sea transp				
	EmS-No.		not applicable		
14 7		ansport in bulk ac	cording to IMO instruments		
		t as bulk according	•		
<u> </u>	•				
		egulatory inform			
15.1.	-		ental regulations/legislation specific	for the substance or mixture	
	EU legislat				
			control of major-accident hazards inv ccording to Directive 2012/18/EU.	olving dangerous substances [Sev	eso-III-Directive
	-		strial emissions [Industrial Emission	s Directivel	
	VOC-value	(in g/L) ISO 11890- (in g/L) ASTM D236	2: 87		
	VOC produc	ct category: (Cat. A	imitation of emissions of volatile org /i) ; VOC limit value: 140 g/l product in a ready to use condition (in g		
	National re	•		(2). 01	
	Restriction	s of occupation	ment for juveniles according to the 'juve	nile work protection guideline' (94/33	/EC).
	Other infor	mation:			
	•		OC) content in percent by weight: 1		
	Denmark: PR-No.:				
45.0		MAL code in mixtur	,		
152	Unemical S	afety Assessment	[		

#### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



XP389R80CK10	AquaSeal NordicWhite	
05.04.2023	Revision date: 17.03.2023	
5.0001	Issue date: 17.03.2023	Page
	05.04.2023	

EN Page 8 / 8

## SECTION 16: Other information

Abbreviations and acronyms				
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road			
OEL	Occupational Exposure Limit Value			
BLV	Biological Limit Value			
CAS	Chemical Abstracts Service			
CLP	Classification, Labelling and Packaging			
CMR	Carcinogenic, Mutagenic and Reprotoxic			
DIN	German Institute for Standardization / German industrial standard			
DNEL	Derived No-Effect Level			
EAKV	European Waste Catalogue Directive			
EC	Effective Concentration			
EC	European Community			
EN	European Standard			
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations			
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk			
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous			
	Goods by Air			
IMDG Code	International Maritime Code for Dangerous Goods			
ISO	International Organization for Standardization			
LC	Lethal Concentration			
LD	Lethal Dose			
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships			
OECD	Organisation for Economic Cooperation and Development			
PBT	persistent, bioaccumulative, toxic			
PNEC	Predicted No Effect Concentration			
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals			
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail			
UN	United Nations			
VOC	Volatile Organic Compounds			
vPvB	very persistent and very bioaccumulative			

#### **Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

\* Data changed compared with the previous version