Technical Data Sheet



Brilliance Neutral Cleaner

BRILLIANCE NEUTRALCLEANER is a cleaning agent to be added to water for damp wiping of finished and oiled hard-wood flooring. It is also suitable for other floors, doors, window frames and plastic surfaces. The product is available as a concentrate.











Giscode: GU50 (concentrate)

ATFA: Compliant NWFA: Compliant MFMA: Compliant

Please note that a finished floor does not only require cleaning but also a maintenance product from time to time. For finished hardwood floors we recommend our care product BRILLIANCE EVERCLEAR.

For basic cleaning of finished floors, we recommend BRILLIANCE CLEANER L94.

Always keep cleaning agents out of reach of children!

For regular maintenance:

Remove dirt using a broom or vacuum cleaner. Damp wipe the floor. Carefully remove sticky dirt with a white pad.

BRILLIANCE NEUTRALCLEANER can also be used in conjunction with the BERGERTOOL SPRAYMOP COMFORTCLEAN.

The concentrate can be mixed at a mixing ratio of 1:200, i.e. 50 ml of concentrate are diluted in 10 l of water, a dilution of 1:100 is recommended – 100 ml concentrate to 10 l of water. 2000 sf/gal

After drying the floor is ready for use.

Storage / transport

Shelf life of original unopened packing 24 months min. provided that material is transported and stored at a cool and dry place.

General remark

Please read the instructions carefully before processing this product. Any use that does not conform to the scope of Berger-Seidle's application is considered improper. The improper use and non-compliance with the instructions in this manual is largely the responsibility of the processor and as a result excludes the manufacturer's liability and warranty. Before using the product, the general conditions for use must be checked properly and professionally.

The following Technical Data Sheets should be observed:

- General instructions of use for hardwood floor finishing
- Cleaning and maintenance of finished/oiled floors
- Identification and safety instructions (MSDS)
- * If the content of the Technical Data Sheet differs from other printed material, e.g. labels, the current version of the Technical Data Sheet on the homepage is always deemed valid. Printed material is always adapted when reprints are