



# EasyFinish

1K waterborne finish

## Unique in its class

Easy application at the performance of a 2K system! EasyFinish has been inspiring contractors and end users in over 60 countries for many years. The outstanding application features and strong performance combine EasyFinish to set the absolute benchmark among 1-component waterborne finishes. Enthusiastic contractors and countless pleased end-consumers speak for themselves year after year.



LOBA – Your partner for surface finishing and care

## Why end users are convinced of EasyFinish:

- Long-lasting beauty of the floor – high resistance to mechanical wear and household chemicals
- Custom choice of appearance – available in satin, semi-gloss and gloss
- Simple and convenient care and maintenance
- Very low emission
- Time saving – light use after 24 hours, fully cured after only 5 days

## Why contractors are enthusiastic about EasyFinish:

- Easy 1K system combined with 2K performance
- Outstanding application qualities – easy to use and safe, no lap marks
- Suitable for almost all wood species as well as cork
- Very low emission, EMICODE® EC2
- EasyFinish semi-gloss combined with LOBACARE SportCare meets the requirements for friction according to DIN 18032 for sports floors.

## Special feature

Take it easy – EasyFinish is known for its outstanding application qualities. In combination with the water-based filler EasyFill and the universal primer EasyPrime, contractors benefit from the highest level of safety and performance!

## Range of use

Suitable for wood and cork floors. For heavy traffic residential areas and commercial use.



<b>Stress level</b>
<div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div><div></div></div> <div>1 2 3 4 5 6 7 8 9 10</div> <div>Residential Commercial Extreme</div>
<b>Art.-no. 11517</b>
<b>Available</b> in satin (1 l, 5 l), semigloss (1 l, 5 l, 10 l), glossy (5 l)
<b>GISCODE W3+</b>
<div><div> UL Listed for use in the US UL Classified for use in the US</div><div> EMICODE EC2 Low Emission</div><div> CONNECTED SYSTEMS</div><div> Green Label Singapore</div></div>
<div><div> A+</div><div> DIN 18032<sup>1)</sup></div></div>

1) semigloss

## Application

- Sand and remove dust from the surface properly
- The use of a primer is recommended (e.g. EasyPrime)
- First coat of EasyFinish with roller Deluxe 120 or Microfiber 100-120
- Can be overcoated within 24 hours without intermediate sanding
- Intermediate sanding after 8-10 hours at the earliest with PerforatedPad P120 or finer; alternatively intermediate sanding with Sanding net P120 or finer
- Second coat of EasyFinish with Roller Deluxe 120 or Microfibre 100-120
- Consumption per coat: 80 - 120 ml/m<sup>2</sup>

LOBA is always at your side and ensures your success with both advice and action. Our experienced experts are happy to support you individually with your projects. Our competent technical service team is at your disposal quickly, if you need hands-on assistance on site. You can always rely on us!

**Please consider the detailed technical information, application advices and set-up recommendations.**

Do you have any questions? Do not hesitate to contact us:

More Information



**LOBA GmbH & Co. KG**

Leonberger Str. 56-62 | 71254 Ditzingen | Germany | Fon: +49 7156 357-0 | Fax: +49 7156 357-211 | E-Mail: [service@loba.de](mailto:service@loba.de) | [www.loba.de/en](http://www.loba.de/en)